

BELLE PCX 1340 4.0H PLATE COMPACTOR



Belle has developed a series of 2 true combination plates for compaction of granular and mixed materials with cohesive content as well as for hot or cold asphalt in confined areas such as parking lots, highways, close to structures, kerbs, and abutments. This plate is designed with improved speed and frequency and with a shortened base plate.

Advantages:

- Foldable mounted guide handle offers superior manoeuvrability and can be lowered to operate under obstacles and close to form work. Reinforced centrifugal clutch ensures longer belt life, and simplified belt adjustment. Lifting points and front lift cage offer easier loading and unloading for operator convenience.
- Large capacity water tank is built into the protective frame.
- Angled holes on spray bar allow complete water coverage over the full width preventing any asphalt pick-up on plate bottom.
- The spray bar is fully protected from damage, easily positioned, with integral paving pad clamp points.

Optional: compact wheel kit, easily fitted and removed Life lubricated vibration bearings

• Code	FC4000E
Model	PCX13-40
Impact Frequency (Num/min)	-
Static Pressure (kg/m ²)	542
Max Power Output kW(ps)	3
Centrifugal Force kN(kgf)	13
Vibration Level (m/min)	3.2
Max Travelling Speed m/min	20
Plate Size (mm) L x W	606 x 400
H	515
W	-
Weight (Kg)	87